

PRODUCT INFORMATION SHEET

SHEEN

FLOOR CLEANER

DESCRIPTION

A clear, non-yellowing, high gloss finish designed to enrich and enhance the natural colours of all types of floors. Conforms to the Australian Standard for the Slip Resistance of Pedestrian Surfaces AS 3661. A simple to use sealer / sealer finish designed for use on a variety of floors from vinyl to terrazzo and timber. Reduces maintenance, inventory and training costs in complex sites such as schools, universities, hospitals and healthcare facilities by simplifying maintenance programs. Also for use in institutional and office environments.

DIRECTIONS

Apply 4 to 6 coats of Sheen to vinyl, terrazzo and timber floors. Preparation: Remove old finish using floor stripper. To improve wetting and cleaning add 1 cup of neutral detergent to stripping solution. Wet scrub the floor using a high productivity black pad. When old finish has been removed pick up with mop and bucket or auto scrubber containing clean potable water. Application: Dry burnish floor before applying sealer. Apply 4 to 6 coats of Sheen to freshly stripped floor. Allow approximately 30 minutes drying time between coats. Maintenance: Dust mop floor daily. Clean with neutral detergent.

SAFETY

NOT HAZARDOUS

PREVENTION: Keep only in original labelled container.

RESPONSE: IF YOU FEEL UNWELL, seek medical advice and show the label whenever possible. IF SWALLOWED: Give a glass of water. IF IN EYES: Hold eyes open, flood with water for at least 15 minutes. if skin contact occurs remove any contaminated clothing and rinse with running water.

STORAGE & DISPOSAL: Store in accordance with local regulatory requirements. Dispose of contents / container in accordance with local regulations. Intended for industrial and commercial use only. For further information refer to the SDS.

EMERGENCY TELEPHONE: POISONS CENTRE 131126

AREAS TO USE

Sealed floors.





Unit 2/659 Boundary Road, Richlands, QLD. 4077